



Certificate of conformity of the factory production control

0036 CPR 91418 102

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Connecting flue pipe, type Metaloterm AD models

| | | |
|---------|-----------|----------------------------|
| model 1 | EN 1856-2 | T600 H1 D V2 L500XX OXXX M |
| model 2 | EN 1856-2 | T600 N1 D V2 L500XX GXXX M |

For details of classification see page 2

produced by

Schiedel Metaloterm B.V.
Oude Veerseweg 23, 4332 SH Middelburg
The Netherlands

in the manufacturing plant

Schiedel Metaloterm B.V.
Oude Veerseweg 23
4332 SH Middelburg / The Netherlands

Ontop Polska Sp. Z o.o.
ul. Hallera 75
98-100 Wiewiórczyn / Poland

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1856-2:2009

under system 2+ are applied and that the factory production control fulfils all the prescribed requirements set out above.

This certificate was first issued on 2020-01-25 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Munich, 2020-01-25

Johannes Steiglechner
Leiter Zertifizierungsstelle Bauprodukte



Connecting flue pipe
Metaloterm AD

EN 1856-2

Model 1

| | |
|---------------|----------------------------|
| DN 130-300* | T600 H1 D V2 L50050 O50 M |
| DN 350-450* | T600 H1 D V2 L50050 O75 M |
| DN 500-600* | T600 H1 D V2 L50060 O100 M |
| DN 700** | T600 H1 D V2 L50060 O200 M |
| DN 800-1000** | T600 H1 D V2 L50080 O200 M |

Model 2

| | |
|---------------|----------------------------|
| DN 130-300* | T600 N1 D V2 L50050 G50 M |
| DN 350-450* | T600 N1 D V2 L50050 G75 M |
| DN 500-600* | T600 N1 D V2 L50060 G100 M |
| DN 700** | T600 N1 D V2 L50060 G200 M |
| DN 800-1000** | T600 N1D V2 L50080 G200 M |

* insulation layer with thickness 37,5 mm (DN 130 – 600)

**insulation layer with thickness 50 mm (DN 700 – 1000)