

Notified Body
Nr. 0036



Industrie Service

Certificate of conformity of the factory production control

0036 CPR 91236 034

Revision 03

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

System Chimney, type Permeter Smooth Air models

model 1, DN 120 - 200	EN 1856-1	T400 N1 D VX LXX050 G75
model 2, DN 120 - 200	EN 1856-1	T450 N1 D VX LXX050 G75
model 3, DN 120 - 200	EN 1856-1	T600 N1 D VX LXX050 G75
model 4, DN 120 - 200	EN 1856-1	T400 N1 D VX LXX050 G50
model 5, DN 120 - 200	EN 1856-1	T450 N1 D VX LXX050 G50
model 6, DN 120 - 200	EN 1856-1	T600 N1 D VX LXX050 G50
model 7, DN 150	EN 1856-1	T600 N1 D VX LXX050 G75

for details of classification see page 2

produced by

Schiedel s.r.o.
Horoušanská 286
250 81 Nehvizdy, Czech Republic

in the manufacturing plants

Schiedel s.r.o.
Modlanská 1
41502 Teplice
Czech Republic

Schiedel Sp. Z o.o.
Okup Wielki, Ul. Inwestycyjna 13
98-100 Łask
Poland

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1856-1:2009

under system 2+ are applied and that the factory production control fulfils all the prescribed requirements set out above.

The determination of the product type on the basis of type testing is documented in: TÜV SÜD Industrie Service GmbH, report no. A 1911-01/12, A 1911-02/13, A 1911-04/18 and A 1399-17/17.

This certificate was first issued on 2013-01-21 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change and the product and the manufacturing conditions in the plant are not modified significantly.

München, 2024-03-25


Johannes Steiglechner
Leiter Zertifizierungsstelle Bauprodukte



System chimney Perimeter Smooth Air	EN 1856-1	
model 1		
DN 120 - DN 200	T400 N1 D V3 L50050 G75	insulation inner liner
DN 120 – DN 200	T400 N1 D V2 L99050 G75	insulation inner liner
model 2		
DN 120 - DN 200	T450 N1 D V3 L50050 G75	insulation inner liner
DN 120 – DN 200	T450 N1 D V2 L99050 G75	insulation inner liner
model 3		
DN 120 - DN 200	T600 N1 D V3 L50050 G75	insulation inner liner
DN 120 – DN 200	T600 N1 D V2 L99050 G75	insulation inner liner
model 4		
DN 120 - DN 200	T400 N1 D V3 L50050 G50	insulation inner and outer liner
DN 120 – DN 200	T400 N1 D V2 L99050 G50	insulation inner and outer liner
model 5		
DN 120 - DN 200	T450 N1 D V3 L50050 G50	insulation inner and outer liner
DN 120 – DN 200	T450 N1 D V2 L99050 G50	insulation inner and outer liner
model 6		
DN 120 - DN 200	T600 N1 D V3 L50050 G50	insulation inner and outer liner
DN 120 – DN 200	T600 N1 D V2 L99050 G50	insulation inner and outer liner
model 7		
DN 150	T600 N1 D V3 L50050 G75	insulation inner and outer liner closed floor passage
DN 150	T600 N1 D V2 L99050 G75	insulation inner and outer liner closed floor passage